QLOCKTWO® EARTH 90

Enjoy time

Instructions for Use



Please read through the instructions carefully for the safe use of the QLOCKTWO EARTH 90 and to ensure its long useful life and keep them in a safe place. The Instructions for Use are also available online: www.glocktwo.com \rightarrow Information

1. Safety Instructions



Please read the Instructions for Use carefully before assembling and using your clock in order to exclude injury to persons and damage to property.



WARNING This product contains magnetic materials. Consult your physician if you wish to know if this may affect the operation of your implanted medical device.

1.1 Scope of delivery

Unpack and check scope of delivery; see the mounting template. Contact your specialised dealer in the event of missing or damaged parts.

1.2 Transport and storage

IMPORTANT Please note the following in order to avoid material damage:

- Use the original packaging.
- Avoid knocking, shaking and vibrating during transportation.
- Two persons must transport the clock. The QLOCKTWO EARTH 90 weighs approx. 25 kg
- Store in dry rooms at room temperature and low humidity.

1.3 Place of installation

IMPORTANT Please note the following in order to avoid material damage:

- Do not use the clock in rooms where humidity is high (e.g. bathrooms).
- Make sure the clock is placed out of the reach of children and animals.
- Do not place the clock directly adjacent to or onto hard drives, computers, mobile phones, credit cards or other electronic components that react sensitively to magnets.
- Position your QLOCKTWO EARTH 90 so that it cannot fall down in the event of unintentional knocks or pulling of the cables.
- Avoid direct heat radiation, for example heat from radiators.
- Avoid direct sunlight.

1.4 Cleaning

Carefully dust surfaces with a soft, dry brush without applying pressure. Please observe the individual care instructions for your front cover at www.glocktwo.com \rightarrow Information

IMPORTANT Polishing cloths or solvents (e.g. turpentine, benzene) or cleaning agents containing alcohol (e.g. spirit) can Cleaning agents containing alcohol (e.g. methylated spirits) can cause damage to the surfaces.

1.5 Maintenance and repairs

Never attempt to repair or dismantle your QLOCKTWO EARTH 90 yourself. Have a specialised dealer or the manufacturer carry out maintenance and repair See the last page of these Instructions for Use for contact details.

1.6 Warranty

The warranty is valid for two years. Only use your QLOCKTWO EARTH 90 with original accessories. Failure to observe the information in these Instructions for Use or modifying, opening or altering your QLOCKTWO EARTH 90 will not be covered by our warranty.

1.7 Disposal

IMPORTANT Improper disposal pollutes the environment.



Electric appliances: Electric appliances may not be disposed of as household waste. Observe regional disposal regulations. Dealers are obliged to take back appliances.




之前

Stainless steel: Stainless steel components are to be recycled as scrap metal. Stainless steel is a valuable raw material which can be melted and reused.

2. Assembly and Connections

2.1 Safe mounting of the clock

WARNING



- Check all cables for visible damage before connecting them to the power supply.
- Have electrical connection carried out by electricians.
- mounting.
- Do not touch cables and plugs with wet hands.

Lay cables so that they cannot be bent or get caught and are not found in passages.

Do not connect your QLOCKTWO EARTH 90 to the power supply in the event of any damage.

Cut off the power supply and check to ensure that there is no voltage before commencing with wall

Comply with acceptable electric data for the power supply, see Section 4 on "Technical Data".

The plug of the power supply unit serves as a disconnecting device from the mains supply. The socket must be located close to the QLOCKTWO EARTH 90 and be easily accessible.

WARNING

Serious crushing and knocks when dropped

- The QLOCKTWO EARTH 90 weighs approx. 25 kg. Two persons must have a safe place to stand when the clock is mounted.
- Scaffolding or a lifting platform is to be provided, depending on the mounting height.
- Choose a standing area height so that the persons can safely hold and mount the QLOCKTWO EARTH 90.
- When inserting the QLOCKTWO EARTH 90 into the wall mounting bracket, make sure that all four suspension bolts are located in the holders and that the QLOCKTWO EARTH 90 engages in the wall mounting bracket.

IMPORTANT Please note the following in order to avoid material damage:

- Observe the load-bearing capacity of the chosen wall and select a suitable fastener for this wall, e.g. dowels and screws for brickwork.
- No supply lines may be present near the drill holes.
- If you feel resistance when hanging your QLOCKTWO EARTH 90 into the wall mounting bracket (e.g. as a result of unfavourably positioned cables), do not use force to press or turn your QLOCKTWO EARTH 90 into the right position. The mains plug can be damaged if the QLOCKTWO EARTH 90 does not engage properly in the wall mounting bracket.
- Use cotton gloves (included with delivery).

2.2 Wall installation

Power supply from a wall connection:


Wall mounting and electrical connection with a wall connection, see the mounting template.

Power supply from a power socket:

Wall mounting, see mounting template.

Proceed as follows for an electrical connection using a power socket:


- \rightarrow Guide the small plug on the mains cable (1) through the cable duct of the wall mounting bracket (2) and plug it into the power supply.
- \rightarrow Push the cable relief of the power supply unit into the cable suspension (3).
- \rightarrow Connect the plug of the power supply to the connection socket of the QLOCKTWO EARTH 90 (4).
- \rightarrow Plug the mains plug into a wall socket (5).



3. Functions and Operation

3.1 Time display and control elements

Time of day shown: 07:18



3.2 Information on setting a time


The time of day can be transferred easily and accurately to the second to your QLOCKTWO EARTH 90 with many smartphones by using the free FLASHSETTER app. More information available at: www.glocktwo.com/flashsetter

QLOCKTWO EARTH 90 can also be set from the front with some instinctive feeling. Touching the [1] 1-minute step button will set the internal counter for seconds at zero. This makes is possible to set the time precisely to the second.

Switching the "IT IS" display on/off:

The factory setting shows the introductory words "IT IS" for full hours and half hours. → If "IT IS" is always shown: Keep button [60] pressed for approx. 3 seconds. \rightarrow Restoring the factory setting: Keep button [60] pressed for approx. 3 seconds.

Control element





Switching the second display on/off:

- The seconds appear in EARTH 90 numbers on the front cover.
- \rightarrow Switching the second display on: Keep the [\diamond] button pressed for approx. 1 second.
- \rightarrow Switching the second display off: Press any button.



Setting the brightness:

The brightness level adapts automatically to the surrounding light in the "automatic mode" (factory setting).

The level of brightness can also be set manually.

- → Press button [☆] repeatedly.
- The settings will change as follows:
- Maximum brightness
- Strong brightness
- Medium brightness
- Low brightness
- Automatic mode (minute dots in the corners light up briefly)

3.3 Infrared remote control (Optional accessories)

Operation:

Settings can all be made with the remote control.

- → Hold the remote control underneath the QLOCKTWO EARTH 90. The infrared receiver is located on the bottom of the casing back.
- \rightarrow Make settings with the remote control. The function of the buttons corresponds to the keys on the back of the casing.

Replacing the battery:


The remote control is operated with a lithium button cell (CR2032). If the transmitting power is low, replace the remote control battery.

Danger- and disposal instructions

- **IMPORTANT** Button cells must be kept out of the reach of children. Medical assistance shall be called upon immediately if button cells are swallowed
- Immediately remove all low powered batteries and dispose of them in accordance with applicable environmental regulations. Replace battery with identical type only.
- If the battery compartment does not close securely, do not use the product and keep it away from children.

3.4 Power failure

The time of day continues to change for approx. 24 hours in the event of power failure. The current time of day will be shown automatically when the power supply has been restored.





4. Technical Data

Model: Dimensions QLOCKTWO EARTH 90 (H × W × D): Wall mounting bracket dimensions $(H \times W \times D)$: Weiaht: Ambient temperature: Remote control, battery: Precision:

supplies could damage the unit.

Power supply unit, input: Power supply unit, output: Connection: QLOCKTWO EARTH 90, input:

Technical data errors and modifications excepted. No liability is assumed for misprints and errors.

QLOCKTWO EARTH 90 900 × 900 × 32 mm 710 × 710 × 38 mm approx. 25 kg +15°C to +30°C CR 2032, 3V ±8 seconds/month

WARNING 100% functionality with included power supply. Only an 18 V power supply unit (54 Watt or sufficiently dimensioned) with the positive pole in the middle of the plug is suitable for this device. Connecting other power

> AC 100 V - 240 V ~ 50/60 Hz. 1.5 A DC 18 V --- 3.0 A ø 5.5 × 2.1 mm DC 18 V ... 400 mA

QLOCKTWO Manufacture GmbH Goethestraße 29, DE-73525 Schwäbisch Gmünd Made in Germany / © All rights reserved www.qlocktwo.com